



# ACRO HP™

## INTERIOR SATIN 1154XX

### Low-Odor Interior Scrub-Resistant Wall Paint

Acro HP is a low odor, high performance 100% acrylic interior coating. Formulated to provide outstanding protection and performance for high-traffic areas. It is an excellent choice for new or previously painted wall and ceiling surfaces including wallboard, plaster, concrete, primed metal and wood surfaces. Acro HP is formulated with an anti-microbial additive, which inhibits the growth of mold and mildew on the surface. A great choice for professional offices, medical and care facilities, or other occupied spaces where low odor and low VOC\* levels are preferred.

#### PRODUCT INFORMATION

<b>Resin:</b>	Acrylic	<b>Weight Per Gallon:</b>	10.69 lbs.
<b>Color Range:</b>	White & Custom Tints	<b>Solids by Weight:</b>	49.47% ± 2%
<b>Finish:</b>	Satin, 10-20 @ 60° (MPI GL3)	<b>Solids by Volume:</b>	35.59% ± 2%
<b>Drying Time:</b>	To Touch: 1 hour	<b>Recommended Film Thickness:</b>	Wet: 4 mils.
<b>(70° F. &amp; 50% R.H.)</b>	To Recoat: 4 hours	<b>Practical Coverage:</b>	Dry: 1.5 mils.
<b>Clean Up:</b>	Water	<b>VOC:</b>	<6 g/L*
<b>Sizes:</b>	Quarts, Gallons, Fives	*Maximum VOC content for non-tinted paint base is less than 6 g/L (40 CFR 59.406). VOC content may increase after tinting product.	
<b>Tint Bases:</b>	White    Deep    Neutral		
	115405   115425   115440		

#### REGULATORY COMPLIANCE

South Coast Air Quality Management District (SCAQMD) Architectural and Industrial Maintenance Coating (AIM - EPA)	GreenSeal GS-11 Standard MPI #145	CDPH 1.2 Std. Emissions Approved California Air Resources Board (CARB)
--	--------------------------------------	---

#### SURFACE PREPARATION

**General:**  
All surfaces must be firm, dry and cleaned free of loose paint, dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. De-gloss shiny surfaces by lightly sanding†. Repair cracks and fill voids.

† See warning for existing lead-based paint under Precautions.

#### New Surfaces:

Follow general surface preparation guidelines. New concrete or stucco must cure for 30 days prior to coating. Moisture content should be less than 12 % as measured with a moisture meter and the pH should be between 7 and 11. Remove all laitance and efflorescence before priming with the appropriate primer.

#### Previously Painted Surfaces:

Follow general surface preparation guidelines. Remove loose or failing paint and spot prime bare areas or entire surface with the appropriate primer. Hard, glossy surfaces may require sanding and/or a bonding primer.

Spraying and backrolling is recommended on new flat work. Do not apply when material, air, and/or surface temperature is below 45°F. To avoid lap marks, maintain a wet edge. Keep product from freezing.

#### APPLICATION

<b>Brush:</b>	Nylon/Polyester Brush
<b>Roller:</b>	3/8" – 3/4" Nap Synthetic Cover
<b>Airless Spray:</b>	.017" - .021" Tip Size

#### RECOMMENDED PRIMERS

<b>Concrete, Stucco, and Masonry:</b>	<ul style="list-style-type: none"> <li>Ph Surfacer Int/Ext Alkali Resistant Primer 620011</li> <li>Super Seal HB Primer 225011</li> </ul>
<b>Concrete Block:</b>	<ul style="list-style-type: none"> <li>Kril Int/Ext Block Filler 481011</li> </ul>
<b>Wood:</b>	<ul style="list-style-type: none"> <li>All Purpose Int/Ext Stain Blocking Primer 470011</li> <li>Trim/Cabinet Undercoater 270011</li> </ul>
<b>Ferrous Metal, Galvanized Metal, or Aluminum:</b>	<ul style="list-style-type: none"> <li>Acrimetel DTM Low Sheen Primer/Finish 310210</li> <li>All Purpose Int/Ext Stain Blocking Primer 470011</li> </ul>
<b>Gypsum Wallboard:</b>	<ul style="list-style-type: none"> <li>Premium PVA Interior Primer 220011</li> <li>Super Seal HB Interior Primer 225011</li> <li>Acro Pure Interior Primer 210011</li> <li>Acrylitex MPI #50 Primer 296017</li> <li>Qwik Prep Plus HB Interior Primer 235011</li> </ul>

OTHER PRIMERS MAY BE APPROPRIATE. CONTACT MILLER PAINT FOR MORE INFORMATION.

#### THINNING

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon. Stir product thoroughly.

#### PRECAUTIONS

**WARNING!** If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. For additional safety information, consult the Material Safety Data Sheet for this product.

**USE ONLY WITH ADEQUATE VENTILATION.**

**KEEP OUT OF REACH OF CHILDREN.**

#### WARRANTY

Miller Paint warrants satisfactory results of our products if used according to label directions. If not satisfied, return the unused portion to place of purchase with a sales receipt. Material will be replaced or purchase price will be refunded. Since we have no control over surface preparation or application, THIS WARRANTY DOES NOT INCLUDE LABOR, THE COST OF LABOR OR INCIDENTAL OR CONSEQUENTIAL DAMAGES ASSOCIATED WITH USE OF THIS PRODUCT. Some states do not allow the exclusion of incidental or consequential damages, so the limitation or exclusion contained in the above warranty may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

#### DISPOSAL

Never pour leftover coating down any sink or drain – use up material on the job or seal can and store safely for future use. Do not incinerate closed containers. For specific disposal or recycle guidelines, contact your local waste management agency or district. Please re-use or recycle.