



PERFORMANCE PLUS®

INTERIOR SEMIGLOSS 1305XX

Interior Wall Paint

Performance Plus is a professional quality interior finish formulated for use on walls and ceilings. Performance Plus is an outstanding product for use on new wallboard, smooth or textured, in living rooms, bedrooms, hallways and ceilings. It is also excellent for use in warehouses, commercial buildings, apartments, homes and other previously painted surfaces such as plaster, wood, masonry, and metal.

PRODUCT INFORMATION

Resin:	Vinyl Acrylic	
Color Range:	White & Custom Tints	
Finish:	Semigloss, 45-55 @ 60° (MPI GL5)	
Drying Time:	To Touch:	1 hour
(70° F. & 50% R.H.)	To Recoat:	4 hours
Clean Up:	Water	
Sizes:	Gallons, Fives	
Tint Bases:	White	Deep
	130505	130525

Weight Per Gallon:	10.5 lbs.
Solids by Weight:	44% ± 2%
Solids by Volume:	31.5% ± 2%
Recommended Film Thickness:	Wet: 4 mils. Dry: 1.2 mils.
Practical Coverage:	250-300 Sq. Ft. Per Gallon
VOC:	<50 g/L*

*Maximum VOC content for non-tinted paint base is less than 50 g/L (ASTM D6886). VOC content may increase after tinting product.

REGULATORY COMPLIANCE

South Coast Air Quality Management District (SCAQMD)
California Air Resources Board (CARB)
Architectural and Industrial Maintenance Coating (AIM - EPA)

GreenSeal GS-11 Standard
MPI #54 / #54X-Green
CDPH 1.2 Std. Emissions Approved

Stock Colors Available:
• Polar White

SURFACE PREPARATION

General:
All surfaces must be firm, dry and cleaned free of loose paint, dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. De-gloss shiny surfaces by lightly sanding†. Repair cracks and fill voids.

†See warning for existing lead-based paint under Precautions.

New Surfaces:

Follow general surface preparation guidelines. New concrete or stucco must cure for 30 days prior to coating. Moisture content should be less than 12 % as measured with a moisture meter and the pH should be between 7 and 11. Remove all laitance and efflorescence before priming with the appropriate primer.

Previously Painted Surfaces:

Follow general surface preparation guidelines. Remove loose or failing paint and spot prime bare areas or entire surface with the appropriate primer. Hard, glossy surfaces may require sanding and/or a bonding primer.

Spraying and backrolling is recommended on new flat work. Do not apply when material, air, and/or surface temperature is below 45°. To avoid lap marks, maintain a wet edge. Keep product from freezing.

APPLICATION

Brush: Nylon/Polyester Brush
Roller: 3/8" – 3/4" Nap Synthetic Cover
Airless Spray: .017" - .021" Tip Size

RECOMMENDED PRIMERS

- Concrete, Stucco, and Masonry:**
 - Kril Int/Ext Alkali Resistant Primer/Sealer 620011
 - Premium Super Seal HB Primer 225011
 - Concrete Block:**
 - Kril Int/Ext Block Filler 481011
 - Wood:**
 - All Purpose Int/Ext Stain Blocking Primer 470011
 - Acrylic Enamel Undercoat 270011
 - Ferrous Metal, Galvanized Metal, or Aluminum:**
 - Acrimetal DTM Low Sheen Primer/Finish 310210
 - All Purpose Int/Ext Stain Blocking Primer 470011
 - Gypsum Wallboard:**
 - Premium PVA Interior Primer/Sealer 220011
 - Premium Super Seal HB Interior Primer/Sealer 225011
 - Acro Pure PVA Interior Primer/Sealer 210011
 - Acrylitex MPI #50 Primer/Sealer 296017
 - Performance Plus HB Interior Primer 235011
- OTHER PRIMERS MAY BE APPROPRIATE. CONTACT MILLER PAINT FOR MORE INFORMATION.*

THINNING

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon. Stir product thoroughly.

PRECAUTIONS

WARNING! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. For additional safety information, consult the Material Safety Data Sheet for this product.

USE ONLY WITH ADEQUATE VENTILATION.

KEEP OUT OF REACH OF CHILDREN.

WARRANTY

Limited Warranty: Miller Paint Company, Inc. warrants to the purchaser that this product will provide satisfactory performance when applied according to label directions. If this product does not perform to specifications, return unused portion along with sales receipt to place of purchase. As the sole remedy to purchaser, dealer will, at its option: provide additional product to correct affected areas, replace with product of equal value or refund the purchase price paid for this paint product. Failures caused by poor surface preparation, improper application or a breakdown of the underlying surface of previous paint film are not covered by this warranty. **THIS WARRANTY SPECIFICALLY EXCLUDES LABOR OR COST OF LABOR OR INCIDENTAL OR CONSEQUENTIAL DAMAGES ASSOCIATED WITH THE USE OF THIS PRODUCT.**

DISPOSAL

Never pour leftover coating down any sink or drain – use up material on the job or seal can and store safely for future use. Do not incinerate closed containers. For specific disposal or recycle guidelines, contact your local waste management agency or district. Please re-use or recycle.