



# PH SURFACER™

(FORMERLY KRIL PRIMER SEALER)

ALKALI RESISTANT PRIMER 620011

## Interior/Exterior Masonry Primer

pH Surfacers is our acrylic penetrating pigmented primer/sealer suitable for exterior or interior use. pH Surfacers is our best primer for concrete and stucco surfaces with alkalinity resistance up to a pH of 13. It can also be used on a variety of above grade surfaces such as non-staining wood, plaster, wallboard, and fiber cement making it a great choice for new construction or for recoating commercial, multi-family, and residential homes.

### PRODUCT INFORMATION

<b>Resin:</b>	Acrylic	<b>Weight Per Gallon:</b>	11.4 lbs.
<b>Color Range:</b>	Whites, Off Whites, Pastels	<b>Solids by Weight:</b>	54% ± 2%
<b>Finish:</b>	<5 @ 60° (MPI GL1)	<b>Solids by Volume:</b>	38% ± 2%
<b>Drying Time:</b>	To Touch: 1 hour To Recoat: 2 hours	<b>Recommended Film Thickness:</b>	Wet: 4 mils Dry: 1 mil
<b>Clean Up:</b>	Water	<b>Practical Coverage:</b>	300-400 Sq. Ft. Per Gallon
<b>Sizes:</b>	Quarts, Gallons, Fives	<b>VOC:</b>	<50 g/L*
<b>Tint Bases:</b>	White 620011	*Maximum VOC content for non-tinted paint base is less than 50 g/L (40 CFR 59.406). VOC content may increase after tinting product.	

### REGULATORY COMPLIANCE

South Coast Air Quality Management District (SCAQMD)  
California Air Resources Board (CARB)  
Architectural and Industrial Maintenance Coating (AIM - EPA)

GreenSeal GS-11 Standard  
MPI #3  
CDPH 1.2 Std. Emissions Approved

### SURFACE PREPARATION

**General:**  
All surfaces must be firm, dry and cleaned free of loose paint, dust, dirt, oil, grease, wax, chalk, rust, mildew or any other contamination or condition that would adversely affect the performance of the coating. De-gloss shiny surfaces by lightly sanding†. Repair cracks and fill voids.

†See warning for existing lead-based paint under Precautions.

#### New Surfaces:

Follow general surface preparation guidelines. New concrete or stucco must cure for 30 days prior to coating. Moisture content should be less than 12 % as measured with a moisture meter and the pH should be between 7 and 11. Remove all laitance and efflorescence before priming with the appropriate primer.

#### Previously Painted Surfaces:

Follow general surface preparation guidelines. Remove loose or failing paint and spot prime bare areas or entire surface with the appropriate primer. Hard, glossy surfaces may require sanding and/or a bonding primer.

### RECOMMENDED TOPCOATS

	EXTERIOR	INTERIOR
<b>Concrete,</b>	· Evolution Exterior	· Evolution Interior
<b>Stucco,</b>	· Acri Lite Exterior	· Acro Pure / Acro HP
<b>Masonry,</b>	· Stratus XT Exterior	· Acrinamel / Acrimax
<b>CMU, Fiber</b>		· Premium Interior
<b>Cement Board, and Wood</b>		

OTHER TOPCOATS MAY BE APPROPRIATE. CONTACT MILLER PAINT FOR MORE INFORMATION.

Spraying and Backrolling recommended on new flat work. To avoid lap marks, maintain a wet edge. Keep product from freezing.

### APPLICATION

**Brush:** Nylon/Polyester Brush  
**Roller:** 3/8" - 3/4" Nap Synthetic Cover  
**Airless Spray:** .017" - .021" Tip Size

### THINNING

Apply at can consistency. If thinning is necessary to maintain workability, do not exceed one-half pint of water per gallon. Stir product thoroughly.

Surface and air temperatures should be between 35°F and 95°F during application and for 48 hours after application. Humidity should be below 80%. Surface temperature should be at least 5°F above dew point. Do not paint if temperatures are expected to drop below 35°F. Do not paint late in the day when excessive dew, condensation, rain, or snow is expected. Large metal surfaces should be painted in temperatures above 50°F.

### PRECAUTIONS

WARNING! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Avoid contact with eyes, skin and clothing. Do not take internally. Wash thoroughly after handling. Close container after each use. For additional safety information, consult the Material Safety Data Sheet for this product.

**USE ONLY WITH ADEQUATE VENTILATION.**

**KEEP OUT OF REACH OF CHILDREN.**

### WARRANTY

Miller Paint warrants satisfactory results of our products if used according to label directions. If not satisfied, return the unused portion to place of purchase with a sales receipt. Material will be replaced or purchase price will be refunded. Since we have no control over surface preparation or application, THIS WARRANTY DOES NOT INCLUDE LABOR, THE COST OF LABOR OR INCIDENTAL OR CONSEQUENTIAL DAMAGES ASSOCIATED WITH USE OF THIS PRODUCT. Some states do not allow the exclusion of incidental or consequential damages, so the limitation or exclusion contained in the above warranty may not apply to you. This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

### DISPOSAL

Never pour leftover coating down any sink or drain – use up material on the job or seal can and store safely for future use. Do not incinerate closed containers. For specific disposal or recycle guidelines, contact your local waste management agency or district. Please re-use or recycle.